

characteristics ESD Labsit 3 with glides and footring

Article: 9121E artificial leather

Dimensions in mm	Backrest:	H:	420
	Seat:	H:	520-770
		B:	450
		T:	420
Packing data	Weight	kg	9,8
	Volume	m³	



Base equipment

Benefit

Lab qualification	Washable and disinfectant-proof GMP-compliant and suitable for clean rooms Can be used in labs in safety class S1 to S3. Joint-free and positive-fit elements (hygienic design).	Suitable for labs and all types of areas where hygiene is critical, as well as use in the healthcare sector, universities, biotechnology, chemistry and pharmaceuticals.
Conductivity	Conductive comfort pad typical leakage resistance of 10 up 6 Ohm. Volume-conducting castors.	Compliant with the ESD properties acc. to DIN EN 61340-5-1.
Handling	Practical handle on backrest. Extremely lightweight. Compact dimensions.	Ensures maximum mobility and simple handling.
Ergonomics	Only a single lever has to be operated for adaptation to the user and workplace situation.	Intuitive handling. Labsit can be automatically adapted with its flex functions. Complicated adjustment tasks are dispensed with.
Backrest	Plastic backrest with 3D flex function.	The backrest is adapted to the movements of the user and gives way when reclining and during lateral rotation of the upper body. Thus ensuring dynamic sitting and optimal body support in every sitting posture. Intuitive and automatic.
Seating surface	Flex function in front edge of seat.	The front edge of the seat is automatically readjusted for leaning forward. As a result, pressure loading is prevented and blood circulation is improved.
Seat shell	Black.	Distinctive appeal. Increase in job quality and employee satisfaction.
Seat pad	ESD faux leather pad Magic Washable, easy-care, disinfectant-proof, soft and comfortable, PVC-free, phthalate-free, resistant to blood and urine. Fire protection acc. to EN 1021 Parts 1+ 2, black colour.	The soft and comfortable pads offer excellent sitting comfort. Washable and sterilisable. Does not contain any softening agents, thus stays soft and comfortable for many years.
Seat height	Seat height setting, infinitely variable from 520 - 770 mm.	Large seat height adjustment range.
Base	Aluminium base.	Very high stability, durable and stable. Elegant and high-quality.
Foot ring	Chrome height-adjustable foot ring.	Provides support thanks to the wide step area and the height can be adjusted simply and quickly.
Glides	Large and abrasion-resistant plastic floor gliders.	High stability.

characteristics ESD Labsit 3 with glides and footring

Article: 9121E artificial leather

Dimensions in mm	Backrest:	H:	420
	Seat:	H:	520-770
		B:	450
		T:	420
Packing data	Weight	kg	9,8
	Volume	m³	



Standards	DIN EN 61340-5-1 DIN EN ISO 14644-1 Air purity class 3 GMP-compliant Lab safety class S1 to S3 Tested for harmful substances DIN 68 877-1 GS certificate for "tested safety" Blue Angel Sanitized Quality management DIN EN ISO 9001 Environmental management DIN EN ISO 14001 Tested environmental management EMAS Industrial safety management OHSAS 18001 EcoVadis CSR Rating 2016 Gold	Verified by certificates from independent testing institutes Procurement security
Guarantee	10-year long-term guarantee, of which 3-year full warranty	Assured quality and high efficiency

characteristics ESD Labsit 3 with glides and footring

Article: 9121E artificial leather

Dimensions in mm	Backrest:	H:	420
		H:	520-770
	Seat:	B:	450
		T:	420
Packing data	Weight	kg	9,8
	Volume	m³	



Options		Benefit
Accessories/Labclip	For simple and individual marking. Can be easily attached and removed at any time	Customizable and can therefore be clearly assigned to an occupier or area.
Armrests	Fixed armrests	Made from plastic